



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : A61F 2/06</p>	<p>A1</p>	<p>(11) International Publication Number: WO 98/31306</p> <p>(43) International Publication Date: 23 July 1998 (23.07.98)</p>
<p>(21) International Application Number: PCT/US98/00866</p> <p>(22) International Filing Date: 16 January 1998 (16.01.98)</p> <p>(30) Priority Data: 08/784,842 17 January 1997 (17.01.97) US</p> <p>(71) Applicant: MEADOX MEDICALS, INC. [US/US]; 112 Bauer Drive, Oakland, NJ 07436 (US).</p> <p>(72) Inventors: LENTZ, David, J.; 140 Hidden Road, Andover, MA 01810 (US). DORMIER, Edward; 17 Lea Place, Rockaway, NJ 07866 (US).</p> <p>(74) Agents: SCOLA, David, A., Jr. et al.; Hoffmann & Baron, LLP, 350 Jericho Turnpike, Jericho, NY 11753 (US).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: PTFE GRAFT-STENT COMPOSITE DEVICE</p> <div data-bbox="289 1136 1284 1507"> </div> <p>(57) Abstract</p> <p>An implantable intraluminal device (10) includes a multilayer composite tubular device (25) supporting one or more stents (28) between the layer thereof. A first porous elongate tube (12) includes an exterior surface and an interior luminal surface. A radially expandable member (28) is disposed about the exterior surface of the first tube. A second porous elongate tube (22) is disposed concentrically over the first tube and is secured thereto so that the radially expandable member is longitudinally immobilized therebetween.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

ePTFE GRAFT- STENT COMPOSITE DEVICE

FIELD OF INVENTION

The present invention relates generally to tubular implantable prosthetic devices such as vascular grafts and other endoprostheses. More particularly, the present invention relates to a graft formed of porous expanded polytetrafluoroethylene (ePTFE) which supports a stent in an ePTFE composite graft-stent device.

BACKGROUND OF THE INVENTION

Intraluminal devices such as grafts and stents are known for treating stenosis, stricture, aneurysms and the like. These devices may be implanted either transluminally in a minimally invasive procedure or may be surgically implanted.

Such intraluminal devices provide a technique for expanding a constricted vessel or for maintaining an open passageway through a vessel. One common technique used to hold open a blocked or constricted vessel such as a blood vessel is to employ a vascular stent. Stents are implantable intraluminal devices typically formed of wire which may be radially expanded to hold open constricted vessels. Thus, wire stents are useful to prevent restenosis of a dilated vessel or to eliminate the danger of reocclusion of the vessel. In addition, wire stents can also be used to reinforce various lumen in danger of collapse. However, stents are not generally designed as conduits or bypass devices.

Intraluminal or endoprosthetic grafts, however, are designed as bypass devices which allow fluid flow therethrough. Often, these devices are percutaneously implanted within the vascular system to reinforce collapsing, partially occluded, weakened or

abnormally dilated localized sections of, e.g., a blood vessel. Grafts may also be surgically implanted by anastomosis to replace a badly damaged portion of vessel.

Vascular grafts may be manufactured from a variety of bio-compatible materials. For example, it is well known to use extruded tubes of polytetrafluoroethylene (PTFE) as vascular grafts. PTFE is particularly suitable as it exhibits superior biocompatibility. PTFE tubes may be used as vascular grafts in the replacement or repair of blood vessels because PTFE exhibits low thrombogenicity. Further, expanded PTFE (ePTFE) tubes have a microporous structure which allows natural tissue ingrowth and cell endothelialization once implanted into the vascular system. This contributes to long term healing and graft patency.

Grafts formed of ePTFE have a fibrous state which is defined by interspaced nodes interconnected by elongated fibrils. The spaces between the node surfaces that are spanned by the fibrils are defined as the internodal distance (IND). The art is replete with examples of vascular grafts made of microporous ePTFE tubes useful as vascular grafts. The porosity of an ePTFE vascular graft is controlled by varying the IND of the microporous structure of the tube. An increase in the IND within a given structure results in enhanced tissue ingrowth, as well as, cell endothelialization along the inner surface thereof. Increasing the porosity of the tubular structure, however, reduces the ability of the graft to retain a suture placed therein during implantation and tends to exhibit low axial tear strength. In order to strike an effective balance between porosity and radial strength, multi-layer ePTFE tubes have been developed. The porosity of these multilayered tubes vary as between the outer and inner layers to achieve a composite structure having sufficient porosity for tissue ingrowth and cell endothelialization while still retaining sufficient radial strength.

It is known in the art to use stents in combination with vascular grafts and other

endoprotheses. Stents may be positioned at one or both ends of a graft to support the graft within a portion of the vessel. Thus positioned, the stents help fix the graft to the vessel wall. In addition, stents serve to keep the lumen open and to anchor the graft in place. A single stent may also be employed in combination with a graft to allow the graft to "float" downstream toward the affected vessel. Once properly positioned, the single stent is expanded to anchor the graft in place.

Several techniques for securing one or more stents to a graft are known. For example, hooks or barbs extending from the stent have been used for securing stents to a graft. Alternatively, a stent may be sutured to a graft. Each of these techniques requires either specialized stent attachment means or secondary procedures to secure the stents to the graft.

Traditional stents have various shapes and sizes depending upon their intended function. For example, structures which have previously been used as stents include coiled stainless steel springs, helically wound coiled springs manufactured from an expandable heat-sensitive material, expanding stainless steel stents formed of stainless steel wire in a "zig-zag" pattern, cage-like devices made from malleable metal, and flexible tubes having a plurality of separate expandable ring-like scaffold members which permit radial expansion of a graft. Each of these devices is designed to be radially compressible and expandable so that it will easily pass through a blood vessel in a collapsed state and can be radially expanded to an implantable size after the target area of the vessel has been reached. Radial expansion and contraction of each of these causes associated longitudinal expansion and contraction of the stent.

Such expandable stents may be supported between the layers of a multi-layer tubular graft. The expandable stent would anchor and support the multi-layer tube within the

lumen. Upon radial expansion, the stent would hold the graft outwardly against the inner wall of the lumen.

One example of such a graft-stent combination is shown in United States Patent No. 5,123,917 issued to Lee et al. A stent-graft combination shown therein includes a plurality of separate scaffold members (stents) mounted between an inner tube and an outer tube forming the multi-layer graft. In one embodiment of this invention, the scaffold members are free floating within an intermediate pocket formed by the inner and outer tubes. In another embodiment, the scaffold members are adhesively affixed to the outer surface of the inner tube. In yet another embodiment of this invention, the inner and outer tubes are adhered to each other in such a manner that separate pockets are formed in which individual scaffold members are placed within each pocket.

In each of these different embodiments of the '917 patent, radial expansion of the scaffold member causes a change in the longitudinal expanse thereof. Thus, a drawback to the device shown in the '917 patent is that the net length of the scaffold member increases as the graft contracts. Accordingly, this increase in the net length of the scaffold member increases the stress forces on the graft as well as tends to delaminate the layers. Thus, these stress forces increase the likelihood that the inner tube will become separated from the outer tube and/or that the graft will tear upon expansion of the scaffold members.

Accordingly, it would be desirable to provide an improved intraluminal device, in particular, an ePTFE graft-stent composite device with improved radial strength that allows for the deployment of a stent and graft simultaneously with the stent already permanently positioned on the graft such that additional stress is not placed on the graft by the stent upon expansion.

SUMMARY OF THE INVENTION

In accordance with the present invention, an improved composite graft-stent device is provided. More particularly, the present invention is formed from two non thrombogenic tubes which are laminated or fused together with one or more stents secured therebetween.

5 This composite device is then expanded to place it in intimate contact with the inner surface of the lumen in which it is positioned.

The composite device is preferably an implantable intraluminal device with a first porous tube that has two opposed ends, an interior luminal surface and an exterior surface. The composite device also contains a second porous tube which is disposed concentrically

10 about the exterior surface of the first tube and is secured to the exterior surface of the first tube. A radially expandable member is disposed about the exterior surface of the first tube and is longitudinally immobilized between the first and second tubes when they are secured. In the present invention, the second tube is secured to the first tube by fusion or by lamination.

15 The radially expandable member between the two tubes includes a longitudinal expanse. As used herein, the term "longitudinal expanse" means the width of the radially expandable member as measured along the axis of the tube. In the present invention, when the member is expanded, there is no distortion along the longitudinal expanse of the member, e.g., the width remains constant as the member is expanded. The member is

20 preferably an expandable stent.

The expandable stent of the invention includes an elongated element with a first end and a second opposed end. In one embodiment of the invention, the elongated element is formed in a generally circular configuration with the first end adjacent to and overlapping

the second opposed end. The stent is expandable through the relative movement of the first end with respect to the second opposed end.

In another embodiment of the invention, the end extent of the first end of the elongated element has a plurality of second end engagement means for engaging the distal end of the second end to provide finite adjustability to the stent.

In yet another embodiment of the present invention, the radially expandable stent includes an elongate element having a first end and a second opposed end. This elongate element is formed in a generally circular configuration with the first and second ends in axial alignment to each other. In this embodiment of the invention, the second end has an elongate open-ended channel wherein radial expansion is achieved by movement of the first end out of the open-ended channel of the second end.

The implantable intraluminal device of the present invention is preferably fabricated out of a biocompatible metal. Most preferably, the implantable intraluminal device is stainless steel, platinum, gold, nitinol, tantalum and alloys thereof.

The first and second tubes of the present invention are preferably fabricated out of a bio-compatible material. Most preferably, the first and second tubes are fabricated out of expanded polytetrafluoroethylene (ePTFE).

In the present invention, a stent may be disposed about the exterior surface of the first tube adjacent to either of the first or second ends. Alternatively, a stent may be disposed about the exterior surface of the first tube at both ends. In yet another embodiment, a plurality of stents may be disposed about the exterior surface of the first tube and longitudinally spaced between stents located at the first and second ends of the device.

In the present invention, the device may be expanded by an inflation force. Preferably, the inflation force is supplied by inflating a balloon catheter.

The process of the present invention hereby incorporates by reference all of the limitations described above for the intraluminal implantable device. By way of summary, in the process of the invention an implantable intraluminal device is provided which includes a first luminal porous tube having first and second ends, an interior luminal surface and an exterior surface. One or more radially expandable members is/are then radially disposed about the exterior surface of the first tube. A second porous tube is then concentrically positioned over the first tube and the radially expandable member(s). The first tube is then secured to the second tube so that one or more expandable members is/are immobilized along the longitudinal axis of the first and second tubes.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention can be further understood with reference to the following description in conjunction with the appended drawings, wherein like elements are provided with the same reference numbers. In the drawings:

FIGURE 1 is a longitudinal cross-section of the composite graft-stent of the present invention.

FIGURE 2 is a front view of the "key-ring" type stent employed in the composite graft-stent of Figure 1.

FIGURE 3 is a front view of another embodiment of a stent of the composite graft-stent of Figure 1.

FIGURE 4 is a front view, partially in section of a still further embodiment of a stent of the composite graft-stent of Figure 1.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Now turning to Fig. 1, a longitudinal cross-section of the preferred embodiment of the graft-stent composite device 10 is shown. This device 10 includes a multilayer graft 25 which is formed of inner and outer tubes 12 and 22 that are preferably formed of expandable polytetrafluoroethylene (ePTFE). Although it is preferred that tubes 12 and 22 be made of ePTFE, any appropriate bio-compatible material, such as porous polyurethane, is also contemplated. Other potential materials for this application include DACRON, a proline mesh or the like. Ideally, the material should be inert and should not promote a significant amount of scar formation.

Graft 25 has first and second opposed ends 14 and 16, respectively. Tube 12 includes an exterior surface 18 and an interior luminal surface 20. Tube 22 has an interior surface 24 and an exterior vascular surface 26. Tube 22 is disposed concentrically over the exterior surface 18 of tube 12 to form the multilayer graft 25.

A plurality of longitudinally spaced stents 28 are disposed between the exterior surface 18 of tube 12 and the interior surface 24 of tube 22. As will be described hereinbelow, each stent 28 is of the type which may be radially expanded. Stents 28 are longitudinally immobilized between tubes 12 and 22 when they are secured to each other. The stents 28 are positioned at spaced locations along the multi-layer graft 25 in numbers which may be selected based on use and application of the device 10.

Fig. 1 shows tubes 12 and 22 laminated together to form graft 25 with stents 28 disposed therebetween. Although Fig. 1 shows tubes 12 and 22 laminated together, any appropriate method of securement, such as fusion, is contemplated. The lamination of tubes 12 and 22 causes stents 28 to be immobilized along the longitudinal axis of the multi-layer graft 25.

Now turning to Fig. 2, a preferred embodiment of stent 28 is shown. Stent 28 may be formed from a wire 30 which is wound in the shape of a simple circle generally described as a "key-ring." The circular wire 30 includes a first end 34 adjacent to and overlapping a second opposed end 36. The wire 30 is radially expandable by movement of first end 34 and second end 36 in opposing directions relative to each other as indicated by arrow A. Radial expansion is accomplished by, for example, the expansion of a balloon catheter exerting radial pressure on wire 30. This radial expansion is achieved without a change in the longitudinal expanse 32 of the wire 30 which is shown in Figure 1. While balloon expansion is described, it is also contemplated that stent 28 may be of the self-expanding variety.

Now with reference to Fig. 3, a further embodiment of the stent of the present invention is shown. Stent 28' may be formed from a wire employing a simple "ratchet" design. The wire 30' is formed in a circular configuration and includes a first end 34' adjacent to and overlapping its second opposed end 36'. Several ratchet-like teeth 38' are located at an end extent 40' of the first end 34'. The other end 36' includes a pawl 41' at a distal end 42' thereof for adjustable engagement with teeth 38'. Upon relative movement of opposed ends 34' and 36', teeth 38' are engaged by pawl 41' to provide adjustable interlocking therebetween. This allows the diameter of the circular stent 28' to be adjustably expanded in incremental fashion, to set the diameter thereof at discrete increments.

Now with reference to Fig. 4, an additional embodiment of a stent is shown. Stent 28" is a wire stent employing telescoping-ends. The wire 30" is formed in a circular configuration and includes a first end 34" that is positioned in general axial alignment with a second opposed end 36". A distal portion 34a" of first end 34" telescopes into an elongate

open-ended channel 44" formed at opposed end 36". The diameter of the stent 28" is contracted and expanded by movement of first end 34" into and out of open-ended channel 44".

5 The various embodiments of each of the stents 28 described herein are preferably manufactured out of a bio-compatible metal. Most preferably, the bio-compatible metal is stainless steel, platinum, gold, nitinol, tantalum and alloys thereof.

One or more such stents 28 may be disposed between tubes 12 and 22. For example, in one embodiment a single stent 28 is disposed about one end of tube 12. In an alternative embodiment of the invention, two stents 28 are disposed about each end of tube 10 12. In yet another embodiment of the invention, several stents 28 are disposed about the exterior surface 18 of tube 12 and are longitudinally spaced therealong between the two ends 14 and 16 of tube 12.

While the preferred embodiments of the invention are shown and described below, other embodiments that fall within the scope of the disclosure and appended claims are also 15 contemplated.

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention and all such modifications are intended to be included within the scope of 20 the following claims.

WHAT IS CLAIMED IS:

1. An implantable intraluminal device comprising:
 - a first porous elongate tube having first and second opposed ends, said first tube having an exterior surface and an interior luminal surface;
 - 5 a radially expandable member disposed about the exterior surface of the first tube; and
 - a second porous elongate tube disposed concentrically over the first tube and secured to the exterior surface thereof; said expandable member being longitudinally immobilized therebetween by said securement of said first and second tubes.
- 10 2. The implantable intraluminal device of claim 1, wherein said radially expandable member includes a longitudinal expanse.
3. The implantable intraluminal device of claim 2, wherein said radially expandable member is expandable without change in said longitudinal expanse.
- 15 4. The implantable intraluminal device of claim 1, wherein said radially expandable member is a radially expandable stent.
- 20 5. The implantable intraluminal device of claim 4, wherein said radially expandable stent comprises an elongate element with a first end and a second opposed end, said elongate element being formed in a generally circular configuration with said first end adjacent to and overlapping said second end.

6. The implantable intraluminal device of claim 5, wherein said first end of said element is moveable with respect to said second end of said element to effect said radial expansion.

5 7. The implantable intraluminal device of claim 5, wherein an end extent of said first end includes a plurality of second end engagement means for engaging a distal end of said second end at plural discrete locations along said end extent for providing finite adjustability therebetween.

10 8. The implantable intraluminal device of claim 4, wherein said radially expandable stent comprises an elongate element with a first end and a second opposed end, said elongate element being formed in a generally circular configuration with said first and second ends of said elongated member being in radial alignment to each other.

15 9. The implantable intraluminal device of claim 8, wherein said second end includes an elongate open-ended channel.

20 10. The implantable intraluminal device of claim 9, wherein said first end of said element is insertable into said opened channel of said second end for movement therein upon radial expansion of said stent.

11. The implantable intraluminal device of claim 4, wherein said stent is a bio-compatible metal.

12. The implantable intraluminal device of claim 11, wherein said bio-compatible metal is selected from the group consisting of stainless steel, platinum, gold, nitinol, tantalum and alloys thereof.

5 13. The implantable intraluminal device of claim 1, wherein said first and second tubes are bio-compatible.

14. The implantable intraluminal device of claim 13, wherein said first and second tubes are expanded polytetrafluoroethylene.

10

15. The implantable intraluminal device of claim 4, wherein said stent is placed adjacent one of said first or second ends.

16. The implantable intraluminal device of claim 4, wherein a first stent is
15 disposed about said first end and a second stent is disposed about said second end.

17. The implantable intraluminal device of claim 16, wherein a plurality of stents are disposed about the exterior surface of said first tube and being longitudinally spaced therealong between said first and second stents.

20

18. The implantable intraluminal device of claim 1, wherein said device is expanded by an inflation force.

19. The implantable intraluminal device of claim 18, wherein said inflation force is supplied by a balloon catheter.

20. The implantable intraluminal device of claim 1, wherein said second tube is secured to said first tube by fusion.

21. The implantable intra-luminal device of claim 1, wherein said second tube is secured to said first tube by lamination.

22. A process for providing an implantable intraluminal device comprising:

a) providing a first porous tube having first and second opposed ends, said first tube having an exterior surface and an interior luminal surface;

b) radially disposing an expandable member about the exterior surface of said first tube;

c) positioning a second porous tube concentrically over said first tube and said expandable member; and

d) securing said first tube to said second tube, wherein said expandable member is immobilized along the longitudinal axis of said first and second tubes.

20

23. The process of claim 22, wherein said expandable member includes a longitudinal expanse.

24. The process of claim 23, wherein said expandable member is expandable without change in said longitudinal expanse.

5 25. The process of claim 22, wherein said expandable member is a radially expandable stent.

26. The process of claim 25, wherein said expandable stent comprises an elongate element with a first end and a second opposed end, said elongate element being formed in a generally circular configuration with said first end adjacent to, and
10 overlapping said second end.

27. The process of claim 26, wherein said expansion is from the relative movement of said first end with respect to said second opposed end.

15 28. The process of claim 26, wherein the end extent of said first end includes a plurality of second end engagement means for engaging the distal end of said second end to provide finite adjustability.

29. The process of claim 25, wherein said radially expandable stent comprises
20 an elongate element with a first end and a second opposed end, said elongate element being formed in a generally circular configuration with said first end and said second opposed end of said elongated member being in axial alignment to each other.

30. The process of claim 29, wherein said second end includes an elongate open-ended channel.

5 31. The process of claim 30, wherein said radial expansion of said member is achieved by movement of said first end in and out of said open-ended channel of said second end.

32. The process of claim 25, wherein said stent is a bio-compatible metal.

10 33. The process of claim 32, wherein said bio-compatible metal is selected from the group consisting of stainless steel, platinum, gold, nitinol, tantalum and alloys thereof.

15 34. The process of claim 22, wherein said first and second tubes are bio-compatible.

35. The process of claim 22, wherein said first and second tubes are expandable polytetrafluoroethylene.

20 36. The process of claim 25, wherein said stent is placed adjacent one of said first or second ends.

37. The process of claim 25, wherein a first stent is disposed about said first

end of said first tube and a second stent is disposed about said second end of said first tube.

38. The process of claim 37, wherein a plurality of stents are disposed about
5 the exterior surface of said first tube and being longitudinally spaced therealong between
said first and second stents.

39. The process of claim 22, wherein said device is expanded by an inflation
force.

10

40. The process of claim 39, wherein said inflation force is supplied by a
balloon catheter.

41. The process of claim 22, wherein said securing is fusion.

15

42. The process of claim 22, wherein said securing is lamination.

1/4

FIG-1




FIG-2




FIG-3





FIG-4



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/00866

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 123 917 A (LEE) 23 June 1992 cited in the application	1-6, 11-13, 15-19, 22-27, 32-34, 36-40
Y	see column 5, line 22 - line 31; figures 1-5 see column 6, line 65 - column 7, line 21; figures 6,7	7-10, 28-31
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

11 May 1998

Date of mailing of the international search report

19/05/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hagberg, A

INTERNATIONAL SEARCH REPORT

Int. Patent Application No.

PCT/US 98/00866

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 28115 A (IMPRA) 19 September 1996 see abstract; figures 1-4,6,7 ---	1-4, 11-14, 18-20, 22-25, 32-35, 39-41
X	EP 0 689 805 A (CORVITA) 3 January 1996 see column 6, line 18 - line 32; figures ---	1-4, 16-19, 22-25, 37-40
Y	EP 0 737 453 A (STACK ET AL.) 16 October 1996 see column 7, line 56 - column 8, line 24; figures 14-16	8-10, 29-31
A	see figures 8,11,17 ---	5,6,26, 27
Y	WO 95 02377 A (SCIMED LIFE SYSTEMS) 26 January 1995 see abstract; figures -----	7,28